

# Avionics

## RDX-7708 Weather Radar Test Set

**AEROFLEX**  
A passion for performance.



### Comprehensive RF Test Set for ARINC 708 Solid State Coherent Weather Radar Systems

- Endorsed by OEM Weather Radar System manufacturers
- Built-in Doppler shift
- Digital readout of output frequency or PRF
- Digital readout of transmitter power PRF controlled manually, or by transmitter or external sync input
- Pulse width manually controlled, equal to transmitter input or 270 microseconds (fixed)

*Aeroflex is a leader in the design, manufacture and marketing of Avionics test systems.*

*The RDX-7708 test sets provide an RF source and monitor for complete RF testing of ARINC 708 T/R (Transmitter/Receiver) units including wind shear variants.*

*Transmitter Power measurement is via a waveguide mounted RF power module. This method minimizes measurement errors due to RF coaxial cable loss variations.*

#### Additional Features

- Range reply selectable in 1  $\mu$ s or 1 mile increments
- RF output adjustable in 1 dBm increments to -127 dBm
- Contour boost in 0.1 dB increments to +20 dB
- Built-in variance modulator

All the above features can be remotely controlled through the IEEE 488-1978 GPIB versions.

- Monitor outputs for detector, spectrum analyzer and sync

### **SPECIFICATIONS**

#### **RDX-7708R, BRW**

#### **REFERENCE RF INPUT**

152.777 MHz

78.6616 MHz

#### **RF OUTPUT (REFERENCE OR VARIABLE)**

#### **FREQUENCY**

#### **RDX-7708 Range**

9295 to 9425 MHz

#### **OUTPUT LEVELS**

#### **Range**

-50 to -127 dBm in 1 dB steps (at 20 dB coupler output)

#### **Accuracy**

$\pm 2$  dB over frequency and attenuation range

For the very latest specifications visit [www.aeroflex.com](http://www.aeroflex.com)

## CONTOUR BOOST

### Range

0 to 19.9 dB for RF outputs  $\leq$  -70 dBm

## DOPPLER OFFSET

### Range

0 to +29 kHz

### Resolution

1 kHz

### RF ON/OFF Ratio

70 dB or greater

## PULSE MODULATION

---

### INTERNAL PRF GENERATOR

### Range

0 to 9999 pps

### Resolution

1 Hz

### OUTPUT PULSE WIDTH

### Range

0 to 99 ms and 270  $\mu$ s (fixed)

### Resolution

0.1  $\mu$ s

### RETURN DELAY

### Range

1 to 999  $\mu$ s or NM

### Resolution

1 unit

## DISPLAYS

---

### FREQUENCY COUNTER

### Accuracy

$\pm$ 3 kHz

### Resolution

1 kHz

### PEAK POWER INDICATOR

### Range

RDX-7708 - 40 to 250 W

### Accuracy

-0.6 dB

### Resolution

1 W

## GENERAL

---

### Dimensions

427 mm wide, 178 mm high, 467 mm deep

16.8 in. wide, 7 in. high, 18.4 in. deep

### Weight

RDX-7708 - 15 kg (33 lbs.)

### Power Requirements

RDX-7708 110/220 VAC, 50-400 Hz

### Power Consumption

100 W

## VERSIONS AND ACCESSORIES

---

When ordering please quote the full ordering number information.

### Ordering Numbers

### Selection Information

RDX-7708BRW X band

RDX-7708CRW Dual reference

### Versions

RDXR RDX-7708R Weather Radar Bench Test (152.777 MHz/GPIB)

RDXBRW RDX-7708BRW Weather Radar Bench Test (78.6616 MHz)

### Accessories (Supplied)

Line Cord

Microwave Coaxial Cable

BNC to BNC Coaxial Cable (Video Detector)

RF Power Module

20 dB Attenuator (RDX-7708 only)

---

For the very latest specifications visit [www.aeroflex.com](http://www.aeroflex.com)

**CHINA Beijing**

Tel: [+86] (10) 6467 2761 2716  
Fax: [+86] (10) 6467 2821

**CHINA Shanghai**

Tel: [+86] (21) 6282 8001  
Fax: [+86] (21) 62828 8002

**FINLAND**

Tel: [+358] (9) 2709 5541  
Fax: [+358] (9) 804 2441

**FRANCE**

Tel: [+33] 1 60 79 96 00  
Fax: [+33] 1 60 77 69 22

**GERMANY**

Tel: [+49] 8131 2926-0  
Fax: [+49] 8131 2926-130

**HONG KONG**

Tel: [+852] 2832 7988  
Fax: [+852] 2834 5364

**INDIA**

Tel: [+91] 80 5115 4501  
Fax: [+91] 80 5115 4502

**KOREA**

Tel: [+82] (2) 3424 2719  
Fax: [+82] (2) 3424 8620

**SCANDINAVIA**

Tel: [+45] 9614 0045  
Fax: [+45] 9614 0047

**SPAIN**

Tel: [+34] (91) 640 11 34  
Fax: [+34] (91) 640 06 40

**UK Burnham**

Tel: [+44] (0) 1682 604455  
Fax: [+44] (0) 1682 662017

**UK Stevenage**

Tel: [+44] (0) 1438 742200  
Fax: [+44] (0) 1438 727601  
Freephone: 0800 282388

**USA**

Tel: [+1] (316) 522 4981  
Fax: [+1] (316) 522 1360  
Toll Free: 800 835 2352



As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2004.

[www.aeroflex.com](http://www.aeroflex.com)  
[info-test@eroflex.com](mailto:info-test@eroflex.com)



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.