

GENERAL SPECIFICATIONS

RECEIVER OPERATION

Ports

2 Independent

Modes

SELECT, ALL

Time Stamp

1 ms resolution

Word Display Format

Binary, HEX, Eng. Units, BCD, User, Graph

Select Word Positions

32

Bus Activity Monitor

Monitors loss of address/word

Real-time Download

RS-232C or 12-bit D/A

TRANSMITTER OPERATION

Ports

1 configurable: version A transmits data and clock on 1 bus only;

Version B transmit data on 1 bus only; Version C transmit data on 1 primary and 1 backup bus

Modes

USER, CONTROLLER compatible transmit mode

Unique Addresses

16

Dynamic Data

10 Words, programmable rise, fall and hold times

Fresh Counter

3 or 4 bit

Software Checksum/CRC

Calculated dynamically

BREAKPOINT OPERATION

Sequence

2: A, B, A or B; A then B

Data Conditions

EQ, NEQ, OR, GT, LT

Trigger Output

5 V, 20 μ S via D/A

Time Stamp

10 ms resolution

Record History

Up to 35,000 programmable about the breakpoint, Event Count1 to 99 before break

Review/Playback

Data display, RS-232, Graph, D/A

RECORD OPERATION

Record History

Up to 55,000 data words, Sample Interval 2 ms to 10 sec

Review/Playback Data display, RS-232, Graph, D/A

GENERAL

Compatibility

ASCB-A, B, and C USER compatible for receive and transmit, controller compatible transmit mode

Database

Preprogrammed ASCB-A, B, and C applications and specifications and custom upload capable via PCMGR-300

Setup Storage

5 RAM tables, 128 FLASH ROM tables (FLASH tables require PCMGR-300)

PHYSICAL CHARACTERISTICS

Weight

3.8 lbs (1.7 kg)

Height

6.5" (16.5 cm)

Width

9.75" (24.7 cm)

Depth

2.0" (5.0 cm)

Display

Super-twist, back-lit LCD; 16-line x 40 characters, 240 x 128 dot graphics

Power Requirements

110-220 VAC Adapter, internal

NiCad battery (4 hours)

Temperature

0 to -50 degrees C operating;

-10 to 60 degrees C storage

ORDERING INFORMATION

DT350H-110 ASCB Databus Analyzer (110V)

DT350H-220 ASCB Databus Analyzer (220V)

Standard Accessories

Battery charger, carrying case, Operations Manual

Optional Accessories

ACPCMGR-300 Software support for the DT350H

Extended Warranty

WDTRC/203C Extended standard warranty 36 months with scheduled calibration

WDTRC/205C Extended standard warranty 60 months with scheduled calibration

CHINA Beijing

Tel: [+86] (10) 6467 2761 2716
Fax: [+86] (10) 6467 2821

CHINA Shanghai

Tel: [+86] (21) 6282 8001
Fax: [+86] (21) 62828 8002

FINLAND

Tel: [+358] (9) 2709 5541
Fax: [+358] (9) 804 2441

FRANCE

Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

GERMANY

Tel: [+49] 8131 2926-0
Fax: [+49] 8131 2926-130

HONG KONG

Tel: [+852] 2832 7988
Fax: [+852] 2834 5364

INDIA

Tel: [+91] 80 5115 4501
Fax: [+91] 80 5115 4502

KOREA

Tel: [+82] (2) 3424 2719
Fax: [+82] (2) 3424 8620

SCANDINAVIA

Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

SPAIN

Tel: [+34] (91) 640 11 34
Fax: [+34] (91) 640 06 40

UK Burnham

Tel: [+44] (0) 1628 604455
Fax: [+44] (0) 1628 662017

UK Stevenage

Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601
Freephone: 0800 282388

USA Wichita

Tel: [+1] (316) 522 4981
Fax: [+1] (316) 522 1360
Toll Free: 800 835 2352

USA JcAIR Test Systems

Tel: [+1] (913) 764 2452
Fax: [+1] (913) 782 5104



As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2005.

www.aeroflex.com
info-test@eroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.