

Avionics

IRS[®] 1200 Automatic Inertial Reference Unit Test System

AEROFLEX
A passion for performance.



The IRS1200 is an inertial reference test system used to test Honeywell Air Data Inertial Reference Units (ADIRU) and Inertial Reference Units (IRU) of air transport, commuter and business aircraft, as well as cockpit control panels and system display units.

With the fully-automated configuration of the IRS1200, an operator can initiate multiple NAV runs and allow the ATE to run overnight with no intervention. The system can be configured for the customer's fleet.

Test Program Sets are delivered complete with (1) LRU Test Unit Adapter (TUA), (2) TUA Self-Test Adapter (not applicable for cockpit devices), (3) Test Program Source and Executable diskettes, (4) Complete Documentation, including TUA design drawings and detailed English language descriptions of test programs, (5) Maintenance and Software Training.

Two Configurations

Automated: 2-Axis Tilt Table

Optional: Manual Tilt Table

Fully Automated Configuration

Unattended Test Operation

Multiple Unattended NAV Runs

Comprehensive Turnkey ATE System Includes

Tilt Table

Power Supplies

Measurement Resources

Test Unit Adapters (TUA)

Test Program Sets

Arinc Databus Resources

Test Control Computer w/ Test Exec. Software

Spares Kit

Software Revision Service

Capable Field Service Engineering staff can provide in-depth training (factory or on-site), installation and expert technical support.

GENERAL SPECIFICATIONS

SHOP POWER REQUIREMENTS

115 to 220V AC / 50 to 60 Hz, +10%

3 phase AC power required for B777 FT-ADIRU/SAARU testing

LINE CURRENT REQUIREMENTS

20 Amps Maximum Surge for Automatic Table

30 Amps Max for Test Station

ENVIRONMENTAL REQUIREMENTS

Temperature

59° to 95° F

15° to 35° C

Relative Humidity

20% to 80%

SHOP AREA REQUIREMENTS FOR A 2-BAY IRS

Width

92" / 234 cm

Depth

85 inches / 216 cm (includes
30" / 77cm for rear access doors)

Height

69 inches / 175 cm

SHOP AREA REQUIREMENTS FOR A 2-AXIS AUTOMATIC TABLE

Width

73.7" / 187.2 cm

Depth

63.7" / 162 cm

Height

48.7" / 123.7 cm

2-axis table weight

2,000 lbs./900 kg

Ideal Aerosmith's 1532 Model, 2-axis positioning tables have been designed to satisfy a wide scope of inertial navigation test requirements. The test table can be programmed to simulate the roll and pitch motions of an aircraft in flight. Each axis can be programmed individually, or simultaneously with the other axes. Rate, accelerations, continuous slewing (clockwise or counterclockwise), reversing and stopping in any position can be easily and rapidly programmed. The user has the option of operating the table manually, if required, for manual positioning and testing.

Programming is accomplished through the IEEE-488 communication buss to the auxiliary controller. The auxiliary controller is used to switch the table from remote to local mode, which allows the table to be operated in local mode by utilizing the touch screen menus to perform various functions such as position, jog, stop and move to the home position. The controller's CRT displays position and velocity, and prompts the user for inputs.

PHYSICAL / ENVIRONMENTAL CHARACTERISTICS

Table top diameter

32" / 81cm (Auto table)

Payload weight

150 lbs./68 kg centered

Table dimensions (auto)

73.7" w x 26" d x 48.7" h

187.2 cm x 66 cm x 123.7 cm

SWING RADIUS ABOUT

Inner axis

28" / 71 cm (auto table)

OPERATING ENVIRONMENT

Temperature

50 to 95 degrees F

10 to 35 degrees C

Relative humidity

5-85%

Total weight

2000 lbs./900 kg (auto table)

Note: The above specifications are for a 2-axis automatic table. For custom specifications or special requirements, please contact Aeroflex, JcAIR Test Systems. We will gladly submit a detailed proposal and quotation for your consideration.

The IRS1200 Inertial Reference Test System has been designed as a replacement for the UG2994 and to test the complete Honeywell IRU/ADIRU product line, including the cockpit control panels and system display units.

The basic version of the IRS1200 is designed to test basic digital IRUs, supporting the following Honeywell part numbers:

HG1050AX	B747-400, F100
HG2001XX	MD-90, F100, RJ
HG1050BX	A300-600, A310
HG1150BX	MD-11
CG1XXX	IRMP, ISDU, MSU, CDU - All Aircraft

The ADIRU expansion to the system is required to test the MD-80 IRU as well as all ADIRUs, giving the system the ability to test these additional Honeywell part numbers:

HG1150AX	A320
HG2030XX	A319, A321, A330, A340
HG2050XX	B737-600/700/800
HG1103BA	MD-90
HG1075, 1086, 1095	Business Jets

A Manual Tilt Table option is available. Operator intervention is required during the testing of units.

The B777 FT-ADIRU/SAARU version of the IRS1200 includes the automated tilt table, as well as considerable additional resources required to test these components. Additional power supplies, data-bus resources (ARINC 429 and 629) and tilt table holding fixtures are required. A Boeing data loader computer is also included to allow capability of downloading new flight software.

Finally, individual Test Program Sets are required for each LRU type. They are maintained in conformance with the test requirements in the Honeywell Component Maintenance Manuals (CMMs). Selected IRU/ADIRU programs have a troubleshooting mode so the user can query the internal BITE memory locations and obtain key internal parameters such as power supply voltages, laser intensity, accelerometer bias, gyro bias, etc. Program source code can be reviewed and modified by the user. Continuous test program updates that track OEM test specification changes can be obtained through our Software Revision Service (SRS).

CHINA Beijing

Tel: [+86] (10) 6467 2761 2716
Fax: [+86] (10) 6467 2821

CHINA Shanghai

Tel: [+86] (21) 6282 8001
Fax: [+86] (21) 62828 8002

FINLAND

Tel: [+358] (9) 2709 5541
Fax: [+358] (9) 804 2441

FRANCE

Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

GERMANY

Tel: [+49] 8131 2926-0
Fax: [+49] 8131 2926-130

HONG KONG

Tel: [+852] 2832 7988
Fax: [+852] 2834 5364

INDIA

Tel: [+91] 80 5115 4501
Fax: [+91] 80 5115 4502

KOREA

Tel: [+82] (2) 3424 2719
Fax: [+82] (2) 3424 8620

SCANDINAVIA

Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

SPAIN

Tel: [+34] (91) 640 11 34
Fax: [+34] (91) 640 06 40

UK Burnham

Tel: [+44] (0) 1628 604455
Fax: [+44] (0) 1628 662017

UK Stevenage

Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601
Freephone: 0800 282388

USA Wichita

Tel: [+1] (316) 522 4981
Fax: [+1] (316) 522 1360
Toll Free: 800 835 2352

USA JcAIR Test Systems

Tel: [+1] (913) 764 2452
Fax: [+1] (913) 782 5104



As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2005.

www.aeroflex.com
info-test@eroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.